

# CK6150 cnc lathe machine

CK6150 cnc lathe machine	
<b>Standard configuration:</b>	<b>USD    FOB</b>
<b>1-----GSK controller</b>	<b>Qingdao port</b>
<b>2-----manual chuck</b>	
<b>3-----manual tailstock</b>	
<b>4---Four station electrical tool post</b>	
<b>5----Processing length 750mm</b>	
<b>Optional configuration:</b>	
<b>1-----Fanuc or Siemens controller</b>	
<b>2-----Pneumatic chuck or hydraulic chuck</b>	
<b>3-----Pneumatic tailstock or hydraulic tailstock</b>	
<b>4-----C axes</b>	
<b>5-----Six station electrical tool post or Eight station electrical tool post</b>	
<b>6-----bar feeder</b>	
<b>7-----center rest and follow rest</b>	
<b>8-----Processing length 1000mm,1500mm,2000mm</b>	

Ms Lisa Du

[lisa@vmclathe.com](mailto:lisa@vmclathe.com)

[cnc1988@aliyun.com](mailto:cnc1988@aliyun.com)

[www.vmclathe.com](http://www.vmclathe.com)

Mobile:+8618263830915

Wechat: +8618263830915

Whatsapp: +8618263830915

Facebook :[www.facebook.com/lisadugreat](http://www.facebook.com/lisadugreat)

Youtube videos:[lisaducnc](https://www.youtube.com/channel/UC...)

itm	unit	CK6150
Max. Swing over bed	MM	500
Max. Swing over cross slide	MM	300
Max. Z axis Travel	MM	750/1000/
Max. X axis Travel	MM	280
Spindle bore	MM	52/82
Spindle nose		ISOA2-8
Spindle speed range	RPM	150-400/300-1000/600-1600 or 200-2000
Spindle speed steps		Independent spindle three gears
Chuck	MM	manual 3 jaws 250
Bed width	MM	400
x/z fast feed	Mm/min	6000/8000
x/z cutting travel speed	Mm/min	1-6000
Number of tool turret		4/6/8
Tool shank type	MM	25*25
Positioning accuracy	MM	X $\leq$ 0.010      Z $\leq$ 0.015
Repeatability Positioning accuracy	MM	X $\leq$ 0.0075      Z $\leq$ 0.010
Min. unit set	MM	0.001
roundness	MM	$\leq$ 0.007
Diameter uniformity	MM	$\leq$ 0.03 Length 300
Flatness	MM	$\leq$ 0.02 diameter 300
Surface roughness		Ra1.6um

Dia. of tailstock sleeve	MM	75
Tailstock sleeve taper		MT5
Max. Tailstock sleeve travel	MM	150
Spindle drive motor power	KW	7.5
Coolant pump power	W	120
size	MM	750mm 2550×1550×1900 mm 1000mm 2750×1550×1900 mm 1500mm 3250×1550×1900 mm 2000mm 3700×1550×1900 mm 3000mm 4710×1550×1900 mm
weight	KGS	750mm NW 2120/ GW 2820 1000mm NW 2240/ GW 3000 1500mm NW 2350/ GW 3200 2000mm NW 2740/ GW 3400 3000mm NW 3600/ GW 4200



