

VMC1060 cnc machining center

VMC1060 cnc machining center	
Standard Configuration:	USD FOB Qingdao port
1----- Fanuc 0i MF controller	
2-----24 tools Taiwan Arm type tool changer	
Optional Configuration:	
1----Taiwan 4th axis	
2---- GSK controller	
2---- Siemens808DA16 controller	
3-----Siemens 828D controller	
4----Mitsubishi M80B controller	
3-----coolant throught spindle	
4---12000 rpm direct drive spindle with oil coolant	
5---- 5 axis-	
6---chain type chip conveyor	
7----Renishaw tool probe	

Ms Lisa Du

lisa@vmclathe.com

cnc1988@aliyun.com

www.vmclathe.com

Mobile:+8618263830915

Wechat: +8618263830915

Whatsapp: +8618263830915

Facebook :www.facebook.com/lisadugreat

Youtube videos:[lisaducnc](https://www.youtube.com/channel/UC...)

ITEM	UNIT	VMC1060
Table Size	MM	1200 X600
Max load	KGS	800
T-Slot size	MM	18 X 5
X-axis	MM	1000
Y-axis	MM	600
Z-axis	MM	550
Spindle nose to table	MM	100-650
Spindle center to z axis guide surface	MM	655
Spindle taper		BT40-150
Spindle speed	RPM	8000
spindle motor power	KW	11/15
X Fast feed	M/MIN	24
Y Fast feed	M/MIN	24
Z Fast feed	M/MIN	20
cutting speed	MM/MIN	1-1000
X feed motor power	N	18
Y feed motor power	N	18
Z feed motor power	N	18
Types tool changers		Arm type tool changer ATC
Capacity of tools		20/24
Tool change time	S	8/2.5
Position Accuracy	MM	±0.006
Repeatability	MM	0.008
machine size	MM	
weight	Kgs	5800 KGS





