

VMC1160 cnc machining center

VMC1160 cnc machining center	
Standard Configuration: 1----- Fanuc 0i MF controller 2-----24 tools Taiwan Arm type tool changer	USD FOB Qingdao port
Optional Configuration: 1----Taiwan 4 th axis 2---- GSK controller 2---- Siemens808DA16 controller 3-----Siemens 828D controller 4----Mitsubishi M80B controller 3-----coolant throught spindle 4---12000 rpm direct drive spindle with oil coolant 5---- 5 axis- 6---chain type chip conveyor 7----Renishaw tool probe	

Ms Lisa Du

lisa@vmclathe.com

cnc1988@aliyun.com

www.vmclathe.com

Mobile:+8618263830915

Wechat: +8618263830915

Whatsapp: +8618263830915

Facebook :www.facebook.com/lisadugreat

Youtube videos:[lisaducnc](https://www.youtube.com/channel/UC...)

ITEM	UNIT	VMC1160
Size	MM	1200 X600
Max load	KGS	800
T-Slot size	MM	18 X 5
X-axis	MM	1100
Y-axis	MM	600
Z-axis	MM	600
Spindle nose to table	MM	100-650
Spindle center to z axis guide surface	MM	655
Spindle taper		BT40-150
Spindle speed	RPM	8000
spindle motor power	KW	11
X Fast feed	M/MIN	24
Y Fast feed	M/MIN	24
Z Fast feed	M/MIN	20
cutting speed	MM/MIN	1-10000
X feed motor power	N	18
Y feed motor power	N	18
Z feed motor power	N	18
Types tool changers		Funnel type tool changer/Arm type tool changer ATC
Capacity of tools		20/24
Tool change time	S	8/2.5
Position Accuracy	MM	±0.006
Repeatability	MM	0.008
machine size	MM	2600 X 2200 X 2500
weight	Kgs	6500



